

TECHNICAL DATA SHEET

7 / 8" RF COAXIAL CABLE

PICASS CABLE 78V



This product is used for mobile network and telecommunication equipment

Material and dimensions

Inner conductor	Copper tube	Ø 9.0 mm
Dielectric	Foam PE	Ø 22.4 mm
Outer conductor	Corrugated copper (Annularly)	Ø 22.9 mm
Jacket	PE, Black, UV resistant, Halogen free	Ø 27.5 mm
Ink marking: metric length: 7/8 " RF Coaxial Cable™ - PICASS - CABLE -78-DD/MM/YY---xxxM		

Documents

UV resistance	GB 14049-093; EN 50289-4-17, Method A
---------------	---------------------------------------

Electrical Specification

Impedance	50 ± 1Ω
Relative Velocity of Propagation	88%
Capacitance	76 pF/m
Inductance	0.19 µH/m
Maximum Operating Frequency	5.0 GHz
Cut-off Frequency	5.2 GHz
Peak Power Rating	91 kW
Insulation Resistance	≥10GΩ x km
DC Breakdown Voltage	10000 V
Jacket Spark Test Voltage	8000 Vrms
Inner Conductor DC-resistance	≤ 1.48 Ω/km
Outer Conductor DC-resistance	≤ 1.45 Ω/km

Environmental Specification

Installation Temperature	-25°C to + 60°C
2011/65/EU (RoHS)	compliant

TECHNICAL DATA SHEET

7 / 8" RF COAXIAL CABLE

PICASS CABLE 78V

Mechanical Specification

Tensile strength	1450 N
Min. bending radius (single)	120mm
Min. bending radius (repeated)	250mm
Number of bends, minimum (typical)	15 (50)
Bending moment	18Nm
Flat plate crush strength	14N/mm
Recommended hanger spacing	1.0m

Standard Conditions

Attenuation, Ambient Temperature	20°C
Average Power, Ambient Temperature	40°C
Average Power, Inner Conductor, Temperature	100°C

Return Loss

Return loss (Band A)	≤ -26dB 800 to 1000MHz
Return loss (Band B)	≤ -24dB 1700 to 1900MHz
Return loss (Band C)	≤ -24dB 1900 to 2200MHz
Return loss (Band D)	≤ -24dB 2200 to 2500MHz
Return loss (Band E)	≤ -24dB 2500 to 3000MHz

Attenuation

Frequency (MHz)	Attenuation (dB/100m)	Average Power (KW)
100	1.17	9.17
200	1.69	6.27
300	2.11	4.51
400	2.48	3.97
450	2.64	3.73
800	3.63	2.48
900	3.86	2.34
1000	4.12	2.19
1800	5.75	1.73
2000	6.11	1.63
2200	6.46	1.40
2500	6.95	1.33
2700	7.28	1.25
3000	7.75	1.16

Maximum attenuation value shall be 105% of the nominal attenuation value
Other frequencies on request